



**TANK SPECIFICATION:**

- BUNDED OIL TANK SUITABLE TO STORE KEROSENE (C1/C2) , FUEL OIL (A2), AND GAS OIL/DIESEL (D), INCLUDING BIO DIESEL (HVO) AS DEFINED IN BSEN2869, BSEN590 AND BSEN15940.
- SUPPLIED WITH 2" BSP FILL POINT FITTED WITH SPILL STOP OVERFILL PREVENTION DEVICE
- 5" INNER TANK INSPECTION LID
- 16" LOCKABLE, HINGED OUTER TANK LID
- 1" BSP FEMALE BOTTOM OUTLET CONNECTION
- BRIMFILL CAPACITY 1024L/225GAL
- FOOT PRINT 610MM X 1860MM

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MM. TOLERANCES ARE: NO DECIMAL ±2 .X ±0.3     ANGLES ±0° 30' .XX ±0.10     ±0° 30'	DRAWN	DATE	<b>FUEL TANK SHOP</b>  TEL: 01643704328 email: sales@fueltankshop.co.uk	
		08 Apr 2020		
	APPROVED		FTS1000 Bunded Tank	
MASS (Kg) 127.39	<b>FTS</b>		SIZE	DRAWING NO.
CAD GENERATED DRAWING, DO NOT MANUALLY UPDATE 3RD ANGLE PROJECTION DO NOT SCALE DRAWING			A3	1001248
			SCALE	SHEET 1 OF 2