



INDIRECT – Diameter 550mm

Product Code	DIEC090I	DIEC120I	DIEC150I	DIEC180I	DIEC200I	DIEC250I	DIEC300I
Capacity (L)	90	120	150	180	200	250	300
Height	750	925	1125	1285	1425	1725	1950
Cold Inlet	186	186	186	186	186	186	186
Heating Flow	180	180	180	180	186	201	201
Return	220	220	300	300	256	361	361
Control Stat	340	340	420	420	446	481	481
Immersion	270	270	350	350	376	411	411
Sec. Return	~	~	~	~	814	1036	1196
T+P Valve	326	508	695	770	915	1140	1310
Standing Heat Loss (W)	43	50	55	68	71	83	94
Standing Heat Loss kWh/24h	1.04	1.2	1.32	1.63	1.7	1.99	2.26
Coil Rating (kW)	17.18	17.76	18.25	19.35	19.94	20.68	23.57
ERP Energy Band	B	B	B	C	C	C	C

DIRECT – Diameter 550mm

Product Code	DIEC090D	DIEC120D	DIEC150D	DIEC180D	DIEC200D	DIEC250D	DIEC300D
Capacity (L)	90	120	150	180	200	250	300
Height	750	925	1125	1285	1425	1725	1950
Cold Inlet	186	186	186	186	186	186	186
Immersion	206	206	206	206	206	206	206
Immersion	~	396	586	675	761	871	970
Sec. Return	~	~	~	~	814	1036	1196
T+P Valve	326	508	695	770	915	1140	1310
Standing Heat Loss (W)	43	50	55	68	71	83	94
Standing Heat Loss kWh/24h	1.04	1.2	1.32	1.63	1.7	1.99	2.26
ERP Energy Band	C	C	C	C	C	C	C