





EMPROTEC EURO 10W-40 LA

Product Code: HDD008 | **Revision:** 20230613



An elite synthetic & low ash heavy duty diesel engine oil.

Available Pack Sizes









Applications

An advanced heavy duty diesel engine oil manufactured from superior quality synthetic base oils. Incorporating our specialist Adaptive Molecular Technology that has been combined with low ash technology to optimise the power and efficiency of your vehicle to help maintain peak reliability to ensure maximum performance and emission compliance.

Recommended by Aztec Oils as suitable for the following applications

ACEA E6/E9 (E7)
API CJ-4
Cummins 20081
Deutz DQC IV-10 LA
JASO DH-2
Mack EO-O Premium Plus
MAN M3575, M3477
Mercedes-Benz 228.51, 228.31
Renault RLD-3, RGD
Volvo VDS-4, VDS-3
Suitable for DAF

Suitable to use for inter-city or long-haul heavy duty diesel engines in commercial, plant, buses and industrial equipment.

Benefits

- Excellent stability offering consistent long-term performance.
- Extended drain capabilities.
- Increased protection against wear and corrosion.
- Low volatility providing reduced oil consumption and emissions
- Suitable for engines with or without exhaust aftertreatment devices.
- Very high levels of engine cleanliness.

Typical Test Data		
Density @ 15°C	ASTM D4052	0.869
Flash Point (°C)	ASTM D92	210
Kinematic Viscosity @ 40°C (mm/s²)	ASTM D445	93
Kinematic Viscosity @ 100°C (mm/s²)	ASTM D445	13.9
Pour Point (°C)	ASTM D97	-36
Total Base Number (mg KOH/g)	ASTM D2896	10
Viscosity Index	ASTM D2207	154

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Health, Safety & Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.





Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.