

## COOLSPEC SUPREME OAT LL50

**Product Code:** WIN005 | **Revision:** 20251103



Longlife MEG antifreeze & coolant, ready-to-use.

### Available Pack Sizes



### Applications

A premium ready-to-use and longlife winter antifreeze and summer coolant, manufactured from high-quality monoethylene glycol (MEG) and a five-year organic acid technology (OAT) inhibitor package. This very versatile product can be used in a variety of combustion engine cooling systems of cars, motorcycles, vans, commercial and agricultural vehicles, also suitable for industrial systems where this type of product is required. Does not contain 2-ethylhexanoic acid (2-EHA), nitrites, amines, phosphates, borates, silicates or other mineral additives.

### Performance Levels

ASTM D3306, D4656, D4985, D6210  
BS 6580:2010  
Chrysler MS 9176  
CNH MAT 3624, MAT 3724  
Cummins CES 14603, 14439  
DAF 74002  
Daimler Truck DTFR 29D110  
Deutz DQC CB-14  
Ford ESD-M97B49-A, WSS-M97B44-D  
GM 1899M, 6277M, 3420, B 040 1065  
IVECO 18-1830  
Jaguar Land Rover STJLR.651.5003  
Leyland Trucks LTS 22 AF 10  
Mack 014GS 17004  
MAN 324 SNF  
Mercedes-Benz 326.3  
NATO S-759  
Opel QL130100  
Renault 41-01-001 Type D  
Rolls Royce Bergen 2.13.01  
Volvo VCS  
VW Group TL-774 D&F (G12, G12 Plus)  
UNE 26361-88  
Suitable to use where G30, G33 & G34 is specified.

### Benefits

- 2-ethylhexanoic acid (2-EHA) free formulation.
- Compatible with rubber & plastics used in the cooling system.
- Effective long-life corrosion protection for all engine materials, including aluminium & ferrous metals.
- Excellent anti-foaming characteristics.
- Meets most international & european standards.
- Superb thermal characteristics that permit effective engine cooling without boiling.
- Suitable for use in internal combustion engines (ICE), hybrids & indirect cooling systems of battery electric vehicles (BEV).
- Universal OAT antifreeze coolant.
- -38°C freeze protection - prediluted and ready to use.

#### Typical Test Data

Appearance		Red/orange liquid
Density @ 20°C	Kg/m <sup>3</sup>	1.09
Equilibrium Reflux Boil Point		172°C
Freezing Point	50% conc. 50% H <sub>2</sub> O	-38°C
Reserve Alkalinity	ml HCl N/10	6.1
pH @ 25°C	50% conc. 50% H <sub>2</sub> O	8.2
Water Content		50%

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

#### Suitable for use in the following applications

John Deere

Cool-Gard II

#### Recommendations

- A Safety Data Sheet is available for consultation at [www.aztecoils.co.uk](http://www.aztecoils.co.uk).
- Before using this product, the vehicles maintenance guide should be checked and changes must be carried out in accordance with the manufacturers' recommendations.
- Contains bittering agent.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures exceeding 30°C & should be kept out of direct sunlight.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.