

1300 Litre Bunded Oil Tanks – Horizontal Oil Storage Tanks

EcoSafe 1300 litre bunded heating oil storage tank with oil level and alarm monitor suitable for new build and existing oil tank installations.



Specifications

Oil Level Alarm Monitor	WatchmanAlarm fitted as standard
Capacity Ltr/Gal	1300/285
Length (mm)	1935
Width (mm)	1265
Height (mm)	1310
Guarantee Period	10 years (one year on components)
OFCERT No	0642109918
Lids	Outer Tank 16" Cap, Inner Tank 4" Inspection Cap
Tank Pack	WatchmanAlarm, PTFE Tape, Heldite, Heldite Applicator, Gate Valve & Filter
Fuel Type	Kerosene (C1/C2), Fuel Oil (A2) and Gas Oil/Diesel (D) as defined in BS2869 and BS EN590 including up to 7% biofuel to BS EN14214
Oulet Size	1"
Overfill Prevention	SpillStop fitted as standard

The Control of Pollution (Oil Storage) (England) Regulations 2001, The Water Environment (Oil Storage) (Scotland) Regulations 2006 and comparable requirements throughout UK and Ireland

Optional Accessory

Tigerloop Oil-De-Aerator OFCERT No 2181080901

Details

EcoSafe is the most advanced range of bunded heating oil tanks in the UK and Ireland. Designed only to store kerosene for central heating oil, they meet and exceed all current oil storage regulations in the UK and equivalent guidelines in Ireland, they are OFCERT certified and manufactured to ISO Standards. They are the brand and range of choice in the industry for over 25 years for strength, reliability and quality. Suitable for domestic, commercial and agricultural installations for new build and existing buildings, they:

- Safeguard property against potential oil spills or ground contamination. The property owner can be liable for expensive clean up costs of an oil spill and which not be covered in the property insurance.
- Provide peace of mind knowing that their oil supply is stored in a good quality and reliable oil tank.
- Monitor level of oil from the comfort of your home or office. Fitted with Watchman Alarm, oil level monitor and alarm monitor, as standard. This remotely monitors the level of oil in the tank and omits an audible alarm if there is a dramatic drop in the level of oil. This electronic device eliminates the need for an external slight gauge or dipstick. It is also available to fit any existing single skin or bunded oil tank.
- Guaranteed for 10 years (component parts for one year)
- Fitted with an overfill prevention device, SpillStop, and a top outlet (on request) providing extra protection against groundwater pollution.