Tel: +44(0)1384 564765 sales@trailereng.com or accounts@trailereng.com www.trailerengineering.co.uk Central Avenue Cradley Heath West Midlands B64 7BY United Kingdom

## 950 LITRE U.N. APPROVED BUNDED JET A1 EU HIGHWAY BOWSER





**CHASSIS:** Constructed from 100 x 50 RSC fully welded with front standing plate and an 'A' frame drawbar. All hot dip galvanised.

**AXLE/SUSPENSION:** Single Knott-Avonride 1500kg torsion beam axle and fitted with 200 x 50 Auto reverse brakes on 4 stud 51/2" pcd hubs

WHEELS AND TYRES: 2 No 185 x 13 x 8 ply radial tyres.

**COUPLING:** Knott-Avonride 2000kg posibrake over run auto reverse c/w spring assisted handbrake lever, breakaway cable & 40mm ring eye or 50mm ball.

**ANCILLARY EQUIPMENT:** Moulded mudguards, mud flaps, rear support stand, telescopic front jockey wheel, Full road lighting c/w 13 pin plug and 7 pin adapter, side reflectors, front reflectors.

**OUTER BUND TANK:** Cylindrical in section constructed from 3mm mild steel, with removable top section for tank access. Rear access door, fitted with stainless steel hinge and fully lockable. Bund contains 110% of inner tank. 4 lifting eyes, fork truck sockets for use when tank is not fitted in a chassis.

**INNER FUEL TANK:** Constructed from translucent heavy duty polyethylene with a capacity of 980 Litres. 2" filler with cap & chain. 1" manual vent valve, 1/2" top mounted suction & return connections. P.R.V. In the top of the tank. Ball valve in base of tank to pump.

**PUMP:** 12v Flameproof Pump. 100AH battery in box, Facet filter monitor, 7m Hose. Bonding Reel, ZVF Trigger Nozzle. Sample Hand Pump Non Resale Flowmeter. **FINISH:** Tank- Primer and two top coats, single British Standard colour. Galvanised Charsin

**DIMENSIONS:** (Approximate)

Width: 1.550m (61") Laden Weight: 1500kg Length: 3.555m (140") Unladen Weight: 476kg Height: 1.524m (60") Towing Height: (Level) 560mm

