

## **2140 LITRE BUNDED ADBLUE EU HIGHWAY BOWSER**

**CHASSIS:** Constructed from 100 x 50 RSC. Fully welded with front standing plate and 'A' frame drawbar. Hot dip galvanised.

**AXLE/SUSPENSION:** Knott-Avonride 3000kg rubber torsion beam fitted with Knott-Avonride 300 x 60 auto reverse brakes operated via cables and rod.

**WHEELS AND TYRES:**

2 No 235/85 x 16 x 12 ply radials fitted to 5 stud 61/2" pcd rims.

**COUPLING:** 3000kg Knott-Avonride posibrake over run auto reverse c/w spring assisted handbrake lever, breakaway cable.

40mm ring eye or 50mm ball.

**ANCILLARY EQUIPMENT:** Moulded mudguards, mud flaps, rear support stand, telescopic front jockey wheel, side reflectors, front markers, full road lighting c/w 13 pin plug and 7 pin adapter.

**OUTER BUND TANK:** Cylindrical in section constructed from 3mm mild steel, with removable top section for tank access. Rear access door fitted with stainless steel hinge and fully lockable. Bund contains 110% of inner tank content. 4 lifting eyes, Fork sockets for use when tank is not fitted in a chassis.

**INNER TANK:** Constructed from translucent heavy duty Polyethylene 2" filler cap and chain. 2" vent valve, Ball valve in base of tank to pump. The Inner Tank is also approved for 10years.

**PUMP:** Rotary hand pump, 15' of 3/4" Adblue hose & trigger nozzle stowed on bracket. All contained within lockable bund area.

Options available on request: Electric Pump, Non Resale Flowmeter.

**FINISH:** Tank- Primer and two top coats, single British Standard colour. Galvanised chassis.

**DIMENSIONS:**(Approximate)

**Width:** 1.981m (78") **Unladen Weight:** 850kg approx

**Length:** 3.684m (145") **Laden Weight:** 2650kg approx – 2800kg max

**Height:** 1.981m ( 78") **Towing Height:** (Level) 590mm

