

Specification Date Sheet | Model: 22EB-EU (W)



(Pump pictured not included)

ENVIROBULKA 2160 Ltr

Envirobulka static, 110% bunded fuel tank, built to BS799 Part 5 & to comply with PPG2 Regulations

- ❖ 110% bunded fuel tank to comply with PPG2 (Pollution Prevention Guidelines) Regulations
- ❖ Manufactured to BS799 Part 5- Specification for Oil Storage Tanks.
- ❖ Fitted with lifting eyes and forkliftable base for ease of handling and relocation of tank (empty only).
- ❖ Secure, lockable bund compartement can house, pump, nozzle, hoses and feed & return connections. Feed and return hoses can be fed thourgh openings enabling generator to be run whilst compartement locked- helps to prevent theft and vandalism.
- ❖ All outlets are mounted above fuel level of helping prevent weepage of fuel. Suction pipe to help remove any fluid from the bund.
- ❖ Inspection cover provides access to inner tank for maintenance and inspection.
- ❖ Steel tank enclosed in steel, weatherproof outer bund- robust, durable product providing secure storage.

SPECIFICATION

Standard Tank Fittings: 2" vent: 2" Fill Points: 3" Auxiliary Fill Point: 1 x 1/2" Generator Feed: 2 x 1/2" Return Ports: 1" Pump Feed: Gauge: 2 x 1 1/4" Ports for additional equipment.			
Capacity (Brim Full) Litres:	2160	Approx. Weight Unladen (kg):	735
Capacity (Brim Full) Gallons:	475	Approx. Weight Laden (kg):	2679*
Dimensions Length (mm):	2098	Design Standards:	BS799 & PPG2
Dimensions Width (mm):	1420	Cabinet dimensions (mm) Opening Size:	Width 855 x Height 450: Depth 451
Dimensions Height (mm):	1499		
Notes			
*Specific gravity of diesel taken 0.9 for this calculation			

Revision Date: 19/02/2015