

OIL SUCTION TRANSFER UNIT

GPS-10

NEW



PUMP TYPE	Suction Solenoid Pump
LIFTING HEIGHT (MAX.)	8 m. vertical (8 mm I.D. tube)
MÁX. HORIZONTAL DISTANCE	100 m. horizontal (8 mm I.D.. tube)
OUTLET FLOW RATING (8 mm I.D. tube)	8 l/hr at: 8 m vertical & 25 m horizontal 15 l/hr at: 5 m vertical & 25 m horizontal
INLET CONNECTION	3/8" F BSP
OUTLET CONNECTION	3/8" F BSP
OVERFLOW OUTLET CONNECTION	1/2" F BSP
POWER SUPPLY	AC 230V, 50Hz
POWER CONSUMPTION	50 W
RESERVOIR TOTAL CAPACITY	3,5 Litre (Maxi: 12 litre)
DIMENSIONS (W x D x H)	240 x 130 x 335 mm (Maxi: 350 x 225 x 345)
WEIGHT	3 kg (Maxi: 4 kg)
FUEL TYPE	Kerosene & Diesel Oil

Optional Fittings

- Double line filter with deaerator for burner return
- Oil collecting tray 400 mm wide with infrared Leak Detector (Schucko plug)
- Oil collecting tray 400 mm wide with infrared Leak Detector (no Schucko plug-wall mounting version)

Product code

01110006003807
23090000004000
23090000004000UK

