

Specification Data Sheet | Model: LLWOB2000



**ENVIROBULKA 9000 Ltr *Low Level Waste Oil Bank***

110% bunded waste oil and hydro-carbon storage tank to comply with PPG2 (Pollution Prevention Guidelines) Regulations

In addition to the standard EnviroBulka benefits, this Deluxe range features:

-  Low level oil collection sump to provide safer, more comfortable working height and help prevent backache.
-  Oil filters and other smaller equipment can be easily drained by placing on the mesh floor above the collection sump.

**OPTIONAL PUMPS**

**VODWOB** – Electric Pump for transfer of waste oil from sump to tank, c/w push-button switch & auto switch-off after 5 min run time. 110 or 240V

**VODWOB-H.** Manual Semi Rotary Hand Pump for transfer of waste oil from sump to tank.

SPECIFICATION			
Standard Tank Fittings: 2" Suction Point : 2" Vent : Sight Glass : Contents Gauge: 2x Spare 1¼" Ports for additional equipment : Bund Drain Pipe : Bund Alarm			
Capacity (Brim Full) Litres:	9000	Weight Unladen (kg):	2750
Capacity (Brim Full) Gallons:	2000	Weight Laden (kg):	18850
Dimensions Length (mm):	2700	Design Standards:	PPG2 & BS799
Dimensions Width (mm):	2300	Cabinet Depth:	680mm
Dimensions Height (mm)	2560		
Notes			

Revision Date: 26/06/2015

