



TABLE 2	DELTA 2 TO 4 Ø1.8m Range (ALL TANKS)		
	INLET INVERT (DIM A)	OUTLET INVERT (DIM B)	OVERALL HEIGHT (DIM C)
0.75m INVERT	750	850	2470
1.0m INVERT	1000	1100	2720

TABLE 1	BIOSAFE Ø1.8m Tank Range		
	DELTA 2	DELTA 3	DELTA 4
Nominal Unit Volume (Litres)	6200	8400	12100
No. Of Turrets	3	3	3
Unit Length (Dim D)	3244	3976	5550
Inlet & Outlet Diameter (Dim E)	110	110	160
Unit Weight (approx)	500Kg	650Kg	800Kg

- NOTES:**
- UNITS ARE AVAILABLE WITH THE INLET INVERTS SHOWN IN TABLE 2. SELECTION OF THE CORRECT INLET INVERT IS KEY, IT MUST BE SUITABLE FOR THE DRAINAGE AND GROUND LEVELS ON SITE. THE INVERT CANNOT BE ALTERED ONCE THE PLANT IS INSTALLED. IN ANY CIRCUMSTANCE, THE MAXIMUM ALLOWABLE INLET INVERT IS 1000mm.
  - IT IS IMPORTANT TO READ AND UNDERSTAND THE INSTALLATION OPERATION & MAINTENANCE GUIDELINES BEFORE ATTEMPTING TO INSTALL THIS UNIT.
  - VENT PIPE CONNECTIONS ARE SUPPLIED BUT VENT RUNS AND STACKS ARE BY OTHERS.

Please Check with Environmental Treatment Systems Limited For The Latest Issue Of This Drawing				
Issue	Date	Drawn by	Approved by	Description
01	03/10/14	M.H.		INITIAL ISSUE

Material : Various  
 Finish :  
 Weight : 649.80 Kg Kgs  
 Modelled By : Name

Tolerance (unless stated) :  
 Thickness : n/a  
 Surface Area : m<sup>2</sup>

**Drawing : DS1134B** Page 1 of 1  
 DELTA 2 - 4 RANGE GENERAL DIMENSIONS

All Dimensions In mm Scale: Do Not Scale  
Third Angle Projection  
 T:\Drawing Data\02 - Sales Drawings\DS\DS - 11\DS1134B

Clearwater reserve the right to alter the details of this drawing without prior notice. This drawing is copyright and may not be reproduced or used without the written permission of Clearwater.

