



Every DESO water storage tank has been engineered to exceed the most demanding technical and regulatory requirements, providing the best water storage solution on the market.

All DESO water tanks are moulded as a one piece tank contributing to the strength and durability of our products. Backed by a 2 year warranty (conditions apply)* your DESO water storage tanks will be an investment you can benefit from for many years.



Potable & Non-Potable Tanks supplied with:



2" BSP male outlets fitted as standard which can be connected into copper, pex, hydrocare etc.



Access point to allow easy access for fitting of ballcocks, floats and extra outlets.



UV Stabilised material

Applications



Water storage for domestic, agricultural or commercial premises



Static above ground installations only



Animal drinking



Vehicle washing



Emergency human consumption

^{*} All DESO water storage tanks must be installed and maintained by a competent person in accordance with manufacturer's instructions and prevailing statutory requirements. DESO will not be responsible for installations that do not conform to these requirements.



Potable and Non-Potable Water Tanks

Potable Water Tank Applications



Specifically designed to store water for emergency human consumption or animal drinking, the DESO potable water tanks are fully recyclable and made from WRAS approved material. They must be installed on a firm, solid flat base and be fully supported.

Non-Potable Water Tank Applications



Designed as a basic water storage tank for non-drinking (not intended for human consumption) use such as vehicle washing, irrigation and washdowns. Must be installed on a firm, solid flat base and be fully supported.



V1675BI K WT/DWT*

- Capacity**: 1675 Litres/368 Gallons
- Diameter: 1410 mm
- Height: 1500 mm
- Outlet: 1" or 2" BSP



V3050BLK WT/DWT*

- Capacity**: 3050 Litres/670 Gallons
- Diameter: 1700 mm
- Height: 1810 mm
- Outlet: 1" or 2" BSP



V1200WT

- Capacity**:1200 Litres/264 Gallons
- Diameter: 1160 mm
- Height: 1270 mm
- Lid: 415 mm Outlet: 1" BSP



V1500WT

- Capacity**: 1500 Litres/330 Gallons
- Diameter: 1100 mm
- Height: 1780 mm
- Lid: 415 mm
- Outlet: 1" BSP



V6250BLK WT/DWT*

- Capacity**: 6250 Litres/1375 Gallons
- Diameter: 2120 mm
- Height: 2300 mm
- Outlet: 2" BSP



V10000BLK WT/DWT*

- Capacity**: 10000 Litres/2200 Gallons
- Diameter: 2260 mm
- Height: 2700 mm
- Outlet: 2" BSP







V12000BLK WT/DWT*

- Capacity**: 12000 Litres/ 2640 Gallons
- Diameter: 2450 mm ■ Height: 3500 mm
- Outlet: 2" BSP



*Non Potable (WT) / Potable (DWT). **Dimensions are approximate only.