



Trailer Engineering Ltd

MANUFACTURERS OF INDUSTRIAL TRAILERS & BOWSERS

Tel: +44(0)1384 564765
sales@trailereng.com or
accounts@trailereng.com
www.trailerengineering.co.uk

Central Avenue
Cradley Heath
West Midlands
B64 7BY
United Kingdom

2000 LITRE ANIMAL FEEDER SITE BOWSER C/W LARGE TROUGH.



CHASSIS Constructed from 5mm pressed steel section fully welded with a 100 x 50 R.S.C 'A' frame drawbar and a front standplate.

AXLE/SUSPENSION Single solid beam axle fitted with 6 stud 205 PCD Hubs

WHEELS/TYRES 2 No. 10.5 X 15 flotation tyres on 6 stud 205 PCD rims.

COUPLING 2" Forged solid ring eye.

TANK Polyethylene moulded tank, elliptical in section, with internal anti surge baffle, 2" front draw off, 2 rear outlet connections, fitted with an 18" lockable outer hinged manlid cover, inner sealed vented manlid. Tank secured to chassis with 2 stainless steel straps.

ANCILLARY EQUIPMENT Front Screwjack.

Atlas Plastics 30 Gallon Double Water Trough. Tough Strong and a leading industry product fitted with B.S Ball valve. Float protect by plastic cover.

Trough Dimensions: - (") 47 x 19 x 11 (mm) 1193 x 482 x 280 Capacity: - 136 Litres/ 30 Gal.

FINISH Poly tank in yellow, green, blue or red (blue drinking water) Galvanised chassis

DIMENSIONS

Width: 1.854m (73")

Length: 3.900m (153")

Height: 1.600m (63")

Unladen weight: 460kg (Approximate)

Laden Max: 2460kg

Towing Height:(Level) 420mm

TRAILER ENGINEERING LTD

Registered Office: HW Accountants, Sterling House, 97 Lichfield Street, Tamworth, Staffordshire. B79 7QF

Registered in England; Company Registration No: 01672152

VAT Registration No: GB 547 2984 06