

Drum Store - DS8VH

Backed by our 20 year structural guarantee*

A pressed steel welded body construction provides the structural strength for this unit, while the roof which is fitted with lifting eyes is manufactured from mild steel. The two easy glide sliding doors are constructed from mild steel and are fitted with a central lock and padlock points (padlocks not supplied).

Constructed from mild steel, the sump is fully seam welded and is as you would expect fully compliant with all current UK regulations relating to sump capacities and the underside is fitted with plinths to eliminate contact with ground and reduce the risk of corrosion. This model holds four 205ltr drums horizontally in cradles on two levels, four 205ltr drums vertically on pallet support beams and has a shelf fitted above the vertical drums for small containers. Prior to painting the unit is fully shot blasted to provide a clean and keyed surface.

*Full details available on request



This model can hold up to 8 x 205ltr drums or 2 x 1000ltr IBC's and will accommodate standard 1200mm x 1200mm, 1200mm x 1000mm and 1200mm x 800mm pallets.

SPECIFICATION

| | |
|----------------------|--|
| External size | 3000mm L x 1500mm W x 2403mm H at the highest point of the unit |
| Internal clear space | N/A |
| Nº of containers | 4 x 205ltr horizontal & 4 x 205ltr vertical + shelf for small containers above the vertical drums |
| Sump capacity | 1125ltr |
| Colour | Green RAL 6029 |
| Tare weight | 1008kg |
| Type of doors | 2 sliding |
| Type of door lock | Keyed handle |
| Access aperture | 1371mm W x 1967mm H (each side) |
| Paint specification | A high build, quick drying primer/topcoat paint specifically designed for use directly on to metal or bare steel, this paint contains zinc phosphate anti-corrosive pigments and is applied with a minimum dry film thickness of 75 microns. |

Chargeable Options:

- Air vents
- Galvanised steel grid mesh
- Galvanised steel pallet channels

Please notify us at the time of ordering if you require any of these options.

