

## Technical Data Sheet | CH-L1F2PG16C6K

### LithiumVault FirePro® Locker Cabinet with Control Panel & Charging | 1-Door | Tall

Cabinet with 6 lockable compartments designed for storing and charging lithium-ion batteries with fire safety features certified for 90-minutes of fire protection, according to EN 14470-1 TYPE 90 standard.

#### Product Characteristics

External Dimensions (WxDxH)	595 x 600 x 2050mm
Internal Dimensions (WxDxH)	496 x 446 x 1540mm
Shelf Dimensions (WxDxH)	495 x 420 x 39mm
Compartment Dimensions (WxDxH)	495 x 400 x 200mm
Number of Shelves	6 x perforated shelves
Doors	1
Door Locks	1 (2 x keys supplied)
Lockers	6
Charging Points	18 (3 x power sockets per shelf)
Tare Weight	210kg (empty cabinets, excl. accessories)
Standard Colour	Black door with grey frame and interior
Socket Options	Type E, type F, type G
Power Phase	Single (10A for Type G)



#### Product Features

- 90-Minutes Fire Rated.
- 6 individually lockable compartments.
- Steel Construction.
- Anti-spark hinges.
- Ventilation.
- Self-closing door system.
- 3A charging sockets with illuminated on/off safety switch.
- 3G2.5mm<sup>2</sup> cable section.
- FirePro® fire detection and automatic extinguishing system with FPC-2V2 control panel.
- Sounder beacon.
- Smoke and heat sensors.
- LPCB Certified to EN 12094-1 and EN 54-2 and 4 and EN 14470-1 TYPE 90.
- Spill tray.
- Voltage: 230V.
- Max amp: 10A for Type G.
- Max power: 2.3kW for Type G.



4 Maxwell Square  
Brucefield Industry Park  
Livingston  
Scotland  
EH54 9BL



distribution@emtez.co.uk



www.romold.co.uk



+44 (0)1506 409 973

